
Thyristor

V_{RRM} = 1600 V
I_{TAV} = 30 A
V_T = 1,4 V


Three Quadrants operation: QI - QIII
1~ Triac


Part number

CMA60MT1600NHB



Backside:Terminal 2





Features / Advantages:

- Triac for line frequency
- Three Quadrants Operation
  - QI - QIII
- Planar passivated chip
- Long-term stability
  of blocking currents and voltages

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-247

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

Terms _Conditions of usage:

The data contained in this product data sheet is exclusively intended for technically trained staff. The user will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to his application. The specifications of our components may not be considered as an assurance of component characteristics. The information in the valid application- and assembly notes must be considered. Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of your product, please contact the sales office, which is responsible for you.
Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.
Should you intend to use the product in aviation, in health or live endangering or life support applications, please notify. For any such application we urgently recommend
- to perform joint risk and quality assessments;
- the conclusion of quality agreements;
- to establish joint measures of an ongoing product survey, and that we may make delivery dependent on the realization of any such measures.


© 2015 IXYS all rights reserved

Rectifier				Ratings			
Symbol	**Definition**	**Conditions**		**min.**	**typ.**	**max.**	**Unit**
$V_{RSM/DSM}$	*max. non-repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1700	V
$V_{RRM/DRM}$	*max. repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1600	V
$I_{R/D}$	*reverse current, drain current*	$V_{R/D}$ = 1600 V	T_{VJ} = 25°C			10	µA
		$V_{R/D}$ = 1600 V	T_{VJ} = 125°C			2	mA
V_T	*forward voltage drop*	I_T = 30 A	T_{VJ} = 25°C			1,40	V
		I_T = 60 A				1,77	V
		I_T = 30 A	T_{VJ} = 125°C			1,40	V
		I_T = 60 A				1,88	V
I_{TAV}	*average forward current*	T_C = 115°C	T_{VJ} = 150°C			30	A
I_{RMS}	*RMS forward current per phase*	180° sine				66	A
V_{T0}	*threshold voltage* } *for power loss calculation only*		T_{VJ} = 150°C			0,90	V
r_T	*slope resistance* }					16,6	mΩ
R_{thJC}	*thermal resistance junction to case*					0,55	K/W
R_{thCH}	*thermal resistance case to heatsink*				0,25		K/W
P_{tot}	*total power dissipation*		T_C = 25°C			230	W
I_{TSM}	*max. forward surge current*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			260	A
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			280	A
		t = 10 ms; (50 Hz), sine	T_{VJ} = 150°C			220	A
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			240	A
I^2t	*value for fusing*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			340	A^2s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			325	A^2s
		t = 10 ms; (50 Hz), sine	T_{VJ} = 150°C			240	A^2s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			240	A^2s
C_J	*junction capacitance*	V_R = 400 V f = 1 MHz	T_{VJ} = 25°C		9		pF
P_{GM}	*max. gate power dissipation*	t_P = 30 µs	T_C = 150°C			10	W
		t_P = 300 µs				5	W
P_{GAV}	*average gate power dissipation*					0,5	W
$(di/dt)_{cr}$	*critical rate of rise of current*	T_{VJ} = 125°C; f = 50 Hz	repetitive, I_T = 90 A			150	A/µs
		t_P = 200 µs; di_G/dt = 0,2 A/µs;					
		I_G = 0,2 A; V = ⅔ V_{DRM}	non-repet., I_T = 30 A			500	A/µs
$(dv/dt)_{cr}$	*critical rate of rise of voltage*	V = ⅔ V_{DRM}	T_{VJ} = 125°C			500	V/µs
		R_{GK} = ∞; method 1 (linear voltage rise)					
V_{GT}	*gate trigger voltage*	V_D = 6 V	T_{VJ} = 25°C			1,3	V
			T_{VJ} = -40°C			1,6	V
I_{GT}	*gate trigger current*	V_D = 6 V	T_{VJ} = 25°C			± 60	mA
			T_{VJ} = -40°C			± 80	mA
V_{GD}	*gate non-trigger voltage*	V_D = ⅔ V_{DRM}	T_{VJ} = 125°C			0,2	V
I_{GD}	*gate non-trigger current*					± 1	mA
I_L	*latching current*	t_p = 10 µs	T_{VJ} = 25°C			90	mA
		I_G = 0,2 A; di_G/dt = 0,2 A/µs					
I_H	*holding current*	V_D = 6 V R_{GK} = ∞	T_{VJ} = 25°C			60	mA
t_{gd}	*gate controlled delay time*	V_D = ½ V_{DRM}	T_{VJ} = 25°C			2	µs
		I_G = 0,5 A; di_G/dt = 0,5 A/µs					
t_q	*turn-off time*	V_R = 100 V; I_T = 30 A; V = ⅔ V_{DRM}	T_{VJ} = 125 °C		150		µs
		di/dt = 10 A/µs dv/dt = 20 V/µs t_p = 200 µs					

© 2015 IXYS all rights reserved

Package TO-247			Ratings			
Symbol	**Definition**	**Conditions**	**min.**	**typ.**	**max.**	**Unit**
I_{RMS}	*RMS current*	per terminal			70	A
T_{VJ}	*virtual junction temperature*		-40		150	°C
T_{op}	*operation temperature*		-40		125	°C
T_{stg}	*storage temperature*		-40		150	°C
Weight				6		g
M_D	*mounting torque*		0,8		1,2	Nm
F_C	*mounting force with clip*		20		120	N

Product Marking




Part description

C = Thyristor (SCR)
M = Thyristor
A = (up to 1800V)
60 = Current Rating [A]
MT = 1~ Triac
1600 = Reverse Voltage [V]
N = Three Quadrants operation: QI - QIII
HB = TO-247AD (3)

Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	CMA60MT1600NHB	CMA60MT1600NHB	Tube	30	516795

Similar Part	Package	Voltage class
CMA60MT1600NHR	ISO247 (3)	1600

Equivalent Circuits for Simulation ** on die level* T_{VJ} = 150 °C




Thyristor


$V_{0\,max}$	*threshold voltage*	0,9	V
$R_{0\,max}$	*slope resistance **	14,1	mΩ

© 2015 IXYS all rights reserved

Outlines TO-247



Sym.	Inches		Millimeter	
	min.	max.	min.	max.
A	0.185	0.209	4.70	5.30
A1	0.087	0.102	2.21	2.59
A2	0.059	0.098	1.50	2.49
D	0.819	0.845	20.79	21.45
E	0.610	0.640	15.48	16.24
E2	0.170	0.216	4.31	5.48
e	0.215 BSC		5.46 BSC	
L	0.780	0.800	19.80	20.30
L1	-	0.177	-	4.49
Ø P	0.140	0.144	3.55	3.65
Q	0.212	0.244	5.38	6.19
S	0.242 BSC		6.14 BSC	
b	0.039	0.055	0.99	1.40
b2	0.065	0.094	1.65	2.39
b4	0.102	0.135	2.59	3.43
c	0.015	0.035	0.38	0.89
D1	0.515	-	13.07	-
D2	0.020	0.053	0.51	1.35
E1	0.530	-	13.45	-
Ø P1	-	0.29	-	7.39



© 2015 IXYS all rights reserved

Thyristor




Fig. 1 Forward characteristics




Fig. 2 Surge overload current
I_{TSM}: crest value, t: duration




Fig. 3 I^2t versus time (1-10 s)




Fig. 4 Gate voltage & gate current




Fig. 5 Gate controlled delay time t_{gd}




Fig. 6 Max. forward current at case temperature





Fig. 7a Power dissipation versus direct output current
Fig. 7b and ambient temperature



i	R_{thi} (K/W)	t_i (s)
1	0.080	0.0100
2	0.060	0.0001
3	0.215	0.0200
4	0.060	0.2000
5	0.135	0.1100

Fig. 7 Transient thermal impedance junction to case

© 2015 IXYS all rights reserved