
SC-RTM-01000-016

Modular IGBT switching rectifier

PRELIMINARY TECHNICAL INFORMATION

HIGHLIGHTS

- Modular construction
- Forced air cooled
- Intuitive interface, clear display
- PLC communication interfaces available
Modbus, Profibus and Profinet



non-contractual image

SC-RTM Series offers a true modular approach for plating rectifiers where each module is fully autonomous, containing both control and power units. Each module can independently manage its operations, and in case of a failure, the faulty module is automatically deactivated. The remaining modules continue to supply the required current and voltage, up to the installed maximum, without any interruption for the user.

This design provides enhanced reliability, as the system can continue to function even if one module fails, and allows for easy replacement of faulty modules within ten minutes by regular maintenance personnel. All connections are plug-and-play, making servicing straightforward.

ELECTRICAL CHARACTERISTICS


Symbol	Parameter	Notes / test conditions	Min	Typ	Max	Units
$V_{AC\ OUT}$	Output voltage		0		16	V_{DC}
$I_{DC\ OUT}$	Rated load		0		1000	A_{DC}
η	Efficiency			84%		
P_{OUT}	Maximum output power				16	kW
V_{SUPP}	Mains supply voltage	*3P+T, 50 Hz*		400		V_{AC}
P_{INP}	Maximum absorbed power				19000	VA
V_{MAINS_ISO}	Mains insulation	*50 Hz @1min*			2500	V_{RMS}
I_{RES}	Current resolution and precision	*0-100% output power range*			±1%	
V_{RES}	Voltage resolution and precision	*5-100% output power range*			±1%	
IP	Protection degree			IP41		
T_{OP}	Operating temperature				40	ºC
%RH	Maximum operation humidity				80	%

OTHER CHARACTERISTICS

Parameter		
Power modules type		IGBT
Digital controller panel		DE100
Available communication PC/PLC (on request)	*Ethernet:*	Profinet, Modbus-TCP
	Serial port:	Profibus, RS485 Modbus-RTU
	Analog signal:	0-10V, 0-20 mA, 4-20 mA
Polarity inversion function		on demand
Shortcircuit protection		x
Overtemperature protection		x
Overvoltage protection		x
Cooling		Forced air
Housing finish / coating		RAL 7035 – Epoxy coating

Reserved the right to change limits, test conditions and dimensions
given in this data sheet at any time without previous notice.

MECHANICAL DIMENSIONS



(All dimensions in mm)

Dimension	Value	Units
Enclosure type	T1	
Width	545	mm
Height	460	mm
Prof.	700	mm
Weight	84	kg

Reserved the right to change limits, test conditions and dimensions
given in this data sheet at any time without previous notice.

Cost Effective Products

SEMICODE ELECTRONICA

Offers to the market a comprehensive range of products from recognized manufacturers at the best price/quality ratio, this products are provided with a basic reference code that allows maintaining the same product reference even if the original device manufacturer is replaced. SEMICODE product reference has to be considered as a generic brand.

Seeking the market needs and trends, we are constantly increasing the product portfolio with new products and suppliers, please ask for the updated information available to our local contacts.

SEMICODE products include semiconductors, passive components and accessories focused in power electronics market.

Datasheet Annotations:

SEMICODE ELECTRONICA annotate datasheets in the top left hard corner of the front page, to indicate product status. The annotations are as follows:
Tentative information: This is the most tentative form of information and represents a very preliminary specification. No actual design work on the product has been started.
Preliminary Information: The product is in design and development. The datasheet represents the product as it is understood but details may change.
Advance Information: The product design is complete and final characterisation for volume production is well in hand.
No Annotation: The product parameters are fixed and the product is available to datasheet specification.

NOTICE: The technical data are to specify components, not to guarantee their properties.No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

© SEMICODE ELECTRONICA. TECHNICAL DOCUMENTATION – NOT FOR RESALE